

SecurView® RT Workstation Technologist Workflow Solutions

SecurView® RT
Technologist Workstation

Workflow Solutions for the Breast Imaging Suite

Our SecurView® RT technologist workstation brings a new level of flexibility and enhanced communication to the breast imaging suite for streamlined workflow and higher patient throughput.

The SecurView RT technologist workstation enables bi-directional electronic communication between the technologist and the physician. Annotations, comments, and instructions can be exchanged in seconds, enhancing workflow.

The SecurView RT manager facilitates efficient networking of multiple technologist workstations, allowing technologists to access studies from multiple workstations and different locations.



SecurView® RT Workstation

Technologist Workflow Solutions

SecurView® RT
Technologist Workstation

SecurView® RT Workstation Specifications

| | |
|-------------------------|---|
| Computer | Workstation Class Hardware, Windows® Based System |
| CPU | High-end Dual Quad Processor |
| Memory | 16GB High Speed RAM Minimum |
| Storage Space | 3.3 TB Minimum |
| Network Interface | 10/100/1000 Base T Ethernet |
| Display Hardware | |
| Monitor | Single 3 Megapixel LCD Display |
| Display Cards | High-end Medical Grade |
| Attached Devices | |
| User Interface | Mouse, Back-lit Keyboard |
| Power | UPS |
| Software | |
| Operating System | Windows 7 |
| Reviewing Software | Dedicated Mammography-based Image Review Software Customized for Technologist Use |
| CAD Display | Integrated (Licensing may be required) |

DICOM Services

Query/Retrieve, Print, Storage

IHE Compliance

Mammography Image Display

Manuals

User Guide

System Configurations

Standalone

System operates as an independent technologist workstation and not as part of the SecurView RT manager. Standalone systems can be reconfigured as client systems.

Client

System will operate with multiple SecurView RT workstations configured with the SecurView RT manager (optional)

SecurView RT Manager Specifications

One SecurView RT manager can support multiple SecurView RT clients, depending on volume and workflow.

| | |
|-------------------|--|
| Computer | Server Class Hardware, Windows Server Based System |
| CPU | High-end Dual Quad Processors available in both tower and rackmount models |
| Memory | 16GB High Speed RAM Minimum |
| Storage Space | 5 TB Minimum |
| Network Interface | 10/100/1000 Base T Ethernet |

Display Hardware

Monitor 21-inch LCD Color Monitor

Attached Devices

User Interface Mouse, Keyboard
Power UPS

Software

Operating System Windows Server 2008
Controlling Software Dedicated Mammography-based, Image Management Software

DICOM Services

Query/Retrieve, Print, Storage

Manuals

User Guide, Installation Manual

Network Requirements

Manager-to-Client Network Connection 100 Base T Ethernet or Faster

Global Headquarters

35 Crosby Drive
Bedford, MA 01730-1401 USA
Tel: +1.781.999.7300
Sales: +1.781.999.7453
Fax: +1.781.280.0668
www.hologic.com